## **NORM5** upright

P/N: 0101037 | RG-RS/N5 600kg 1200/500





## **Technical data**

Modular dimension: 150 mm

Max. section load 600

**Weight:** 3.286 kg

Width: 25 mm

**Depth:** 500 mm

Height: 1210 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of  $1.0 \times 1.0$ " (25 × 25 mm) square tubes, connected and stabilised by press-fitted  $2.0 \times 0.08$ " (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded Ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request: 09.05.2024, 17:22:44

All information / dimensions are approximate, technical changes reserved. © Hupfer