## **NORM5** upright

P/N: 0101287 | RG-RS/N5 600kg 2000/300





Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

**Modular dimension:** 150 mm

Max. section load 600

**Carbon footprint (TM65 Basic Report)** 44 kgCO□e

Weight: 4 kg

Width: 300 mm

**Depth:** 25 mm

Height: 1960 mm

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of  $1.0 \times 1.0$ " (25 × 25 mm) square tubes, connected and stabilised by press-fitted  $2.0 \times 0.08$ " (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded Ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request: 18.04.2025, 21:27:31

All information / dimensions are approximate, technical changes reserved. © Hupfer