General purpose trolley side panel 2 shelves 800×500 mm



P/N: 0111934 | GSW 8x5/2



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Payload: 80 kg

Weight: 33 kg

Width: 900 mm

Depth: 600 mm

Height: 950 mm

Serving trolley in closed version with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. \emptyset 1.0" (25 mm) round tube frame with 2 welded, 31.5 × 19.7" (800 × 500 mm) deep-drawn shelves with 0.4" (10 mm) high profile edge, lined with sound insulation on the underside, hygienically folded by 1.4" (35 mm) and rebated inwards, designed for easy cleaning. Push bars integrated on both sides into tube frame ensure good manoeuvrability. Trolley with stainless steel panels on three sides and double-wing doors with grip opening and magnetic catch. 4 polypropylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, \emptyset 4.9" (125 mm), chrome-galvanised housing, plastic caster wheel with roller bearing, failsafe running tread identical to pneumatic casters, with pin fastening.

Time and date of the request: 17.08.2025, 06:06:54

All information / dimensions are approximate, technical changes reserved. © Hupfer