

Gastronorm trolley for 18×GN 1/1

P/N: 0112775 | RWG 1/18 GN 75-L-U

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension:	75 mm
Insertion type:	Lengthwise insertion
Payload:	90 kg
Weight:	19 kg
Width:	454 mm
Depth:	619 mm
Height:	1662 mm

The shelving trolley is used for transporting, temporarily storing, preparing, and distributing GN containers.

Trolley with one compartment in robust, self-supporting and hygienic design, made of high-quality 1.0 × 1.0" (25 × 25 mm) stainless steel. 18 pairs of welded U-shaped shelf rails at distances of 3.0" (75 mm), with push-through and tilt protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8 × 0.4" (20 × 10 mm) rectangular-profile cross braces ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

- Extensive equipment options allow for customised design and individual usage possibilities
- The design of the rails ensures safe insertion and removal of GN containers
- Swivel castors provide smooth driving and precise manoeuvring
- Locking devices guarantee secure driving and positioning
- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Valuable materials ensure sustainability and value retention
- Robust construction guarantees high stability and load capacity

Time and date of the request:
20.04.2026, 15:05:05

All information / dimensions are approximate, technical changes reserved. © Hupfer