

Transport shelving unit for self-assembly for shelves 1000×600 mm

P/N: 0121404 | RTW/Z 10-6/1200

HUPFER
we make work flow



Technical data

| | |
|-----------------|---------|
| Payload: | 200 kg |
| Weight: | 17 kg |
| Width: | 1075 mm |
| Depth: | 675 mm |
| Height: | 1200 mm |

Similar to illustration, technical modifications reserved. Without decoration.

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

Time and date of the request:
17.08.2025, 18:23:57

All information / dimensions are approximate, technical changes reserved. © Hupfer