

Transport shelving unit

P/N: 0121405 | RTW/Z 12-5/1200

HUPFER
we make work flow



Technical data

Modular dimension:	150 mm
Payload:	200 kg
Weight:	18 kg
Width:	1275 mm
Depth:	575 mm
Height:	1200 mm

Similar to illustration, technical modifications reserved. Without decoration.

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1200 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:
04.04.2025, 17:39:52

All information / dimensions are approximate, technical changes reserved. © Hupfer