Transport shelving unit for self-assembly for shelves 1300×500 mm



P/N: 0121414 | RTW/Z 13-5/900



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension: 150 mm

Payload: 200 kg

Weight: 19 kg

Width: 1375 mm

Depth: 575 mm

Height: 900 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0×1.0 " (25×25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.12 " (50×3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four $2.0 \times 0.8 \times 0.06$ " ($50 \times 20 \times 1.5$ mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 23.05.2025, 21:58:49

All information / dimensions are approximate, technical changes reserved. © Hupfer