## Transport shelving unit for self-assembly for shelves 1200×500 mm



P/N: 0123094 | RTW/Z 12-5/1652



## 9

Similar to illustration, technical modifications

reserved. Without decoration.

## **Technical data**

Payload: 200 kg

Weight: 18 kg

**Width:** 1270 mm

**Depth:** 570 mm

Height: 1652 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of  $1.0 \times 1.0$ " (25 × 25 mm) square tubes, connected and stabilised by press-fitted  $2.0 \times 0.12$ " (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four  $2.0 \times 0.8 \times 0.06$ " (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

Time and date of the request: 18.08.2025, 14:47:06

All information / dimensions are approximate, technical changes reserved. © Hupfer