## Norm 35 upright 1800×510 mm

P/N: 0126002 | RG-RS/N35 1800/510





## ,

Similar to illustration, technical modifications

reserved. Without decoration.

## **Technical data**

**Modular dimension:** 150 mm

Max. section load 2000

Carbon footprint (TM65 Basic Report) 88 kgCO□e

Weight: 9 kg

Width: 510 mm

**Depth:** 30 mm

Height: 1800 mm

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1.  $2 \times 1$ . 2" (30  $\times$  30 mm) square tubes, connected by welded upright spokes made of  $2.4 \times 0.16$ " (60  $\times$  4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and height-adjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Time and date of the request: 22.08.2025, 12:31:18

All information / dimensions are approximate, technical changes reserved. © Hupfer