Norm 35 upright 2000×510 mm

P/N: 0126042 | RG-RS/N35 2000/510





Technical data

Modular dimension: 150 mm

Max. section load 2000

Carbon footprint (TM65 Basic Report) 93 kgCO□e

Weight: 9 kg

Width: 510 mm

Depth: 30 mm

Height: 2000 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1. 2×1 . 2" (30 \times 30 mm) square tubes, connected by welded upright spokes made of 2.4×0.16 " (60 \times 4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and height-adjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Time and date of the request: 21.08.2025, 18:56:35

All information / dimensions are approximate, technical changes reserved. © Hupfer