Norm 25 upright 1800×600 mm

P/N: 0137005 | RG-RS/N25 600kg 1800/600



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension: 150 mm

Max. section load 600

Carbon footprint (TM65 Midlevel Report) 40 kgCO□e

TM65 Midlevel Report Link to the certificate

Weight: 4 kg

Width: 600 mm

Depth: 25 mm

Height: 1810 mm

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0×1.0 " (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.08 " (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded Ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request: 12.12.2025, 23:22:57

All information / dimensions are approximate, technical changes reserved. © Hupfer