

# Norm 25 upright 1800×400 mm

P/N: 0137007 | RG-RS/N25 600kg 1800/400

**HUPFER**  
we make work flow



*Similar to illustration, technical modifications reserved. Without decoration.*

## Technical data

<b>Modular dimension:</b>	150 mm
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Midlevel Report)</b>	42 kgCO <sub>2</sub> e
<b>TM65 Midlevel Report</b>	<a href="#">Link to the certificate</a>
<b>Weight:</b>	4 kg
<b>Width:</b>	400 mm
<b>Depth:</b>	25 mm
<b>Height:</b>	1810 mm

Modular shelving system made of high-quality stainless steel in hygienic construction according to DIN 18868-2, suitable for continuous use at temperatures from -40 °C to +60 °C, for installation in a straight line or as corner construction with corner connection brackets, extendable in length as required.

Shelf stand made of square tubes 25 × 25 mm, connected and stabilised by firmly pressed cross-running support rungs 50 × 2 mm. Upper cover caps made of plastic and height-adjustable screw feet to compensate for floor unevenness up to 25 mm as a hygienic finish of the shelf stand. Firmly welded support pins ø 7 mm at a distance of 150 mm for easy hanging of the shelf boards.

Time and date of the request:  
26.03.2026, 02:48:01

*All information / dimensions are approximate, technical changes reserved. © Hupfer*