## Swivel castor with lock □125 mm

P/N: 014000402 | LR Poly P3/125 mF





## Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

Payload: 100 kg

Weight: 0.7 kg

Width: 130 mm

**Depth:** 59 mm

Height: 165 mm

The swivel castor with brake is designed for attachment to mobile devices. The swivel castor with brake enables the mobility, steering, and control of the devices.

The easy-running swivel caster with brake made of high-quality plastic with stainless steel components is corrosion-resistant and is intended for attachment to movable equipment. The Hupfer swivel caster ensures the mobility of movable devices. The effortless turning, steering, and positioning of the equipment using the swivel casters increase the efficiency and safety of performing tasks in tight or crowded work areas. The robust swivel caster is equipped with a swivel bearing with a double ball race and allows for effortless handling of the equipment, even with heavy loads. The wheel body is made of high-quality plastic and the tread is made of thermoplastic rubber. The swivel caster protects surfaces and ensures a flawless environment. The precision ball bearing and thread guard enable near-silent and smooth mobility. The brakes ensure the securing and stabilisation of the device's position. The swivel caster is securely mounted to the device using a mounting plate, providing stability.

- Durable plastic housing ensures longevity - Swivel bearing with double ball race allows for effortless movement and precise control - Precision bearings and thread protection ensure near-silent and smooth operation - Locking devices guarantee the securing and stabilisation of the device's position

Time and date of the request: 15.06.2025, 23:45:21

All information / dimensions are approximate, technical changes reserved. © Hupfer