

Plate dispenser with fan-assisted heating up to 100 °C

P/N: 0161590 | TE/UH 2/19-26 VC

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity:	Up to 130 parts w/o cover, 138 parts with cover
Payload:	140 kg
Capacity:	2000 W
Supply voltage:	AC 220-230 V
Nominal current:	8,6 A
Protection class:	Class I
Frequency:	50/60 Hz
Weight:	54 kg
Width:	960 mm
Depth:	510 mm
Height:	970 mm

Plate dispenser for storing \varnothing 7.5-10. 2" (190-260 mm) round plates in two stacking compartments heated with circulating air.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Inner panelling on all sides, with high-quality mirror sheets for optimised energy usage. Open stacking compartments and stacking platforms in electropolished stainless steel rod design. Three crockery guides per stacking compartment made of electropolished stainless steel, variably adjustable without tools. Consistent output heights thanks to manually adjustable stainless steel tension spring systems. Easy cleaning of stacking compartments from above. Reduced temperature losses and heating time thanks to cover hoods made of polycarbonate with 3-point locking mechanism. Heated by power module with integrated motor, fan impeller and stainless steel tubular heating element for automatic convection air operation, operated using On/Off switch with integrated indicator light, thermostat-controlled using a continuously variable, ergonomically-shaped thermostat that is easy to read even from a distance, with temperature limiter as per VDE. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four massive polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, \varnothing 4.9" (125 mm), fastened by means of screw-on plates and several screws.

Time and date of the request: 04.04.2025, 22:52:29 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

Plate dispenser with fan-assisted heating up to 100 °C

P/N: 0161590 | TE/UH 2/19-26 VC

HUPFER
we make work flow

The Hupfer plate dispenser TE/UH 2x19-26 VC has two push handles installed on the corners of the unit to ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution. In addition, it features the highest heating capacity in comparison to other products, allowing it to reach the highest possible crockery temperature.

Time and date of the request:
04.04.2025, 22:52:29

All information / dimensions are approximate, technical changes reserved. © Hupfer