

Cutlery soak sink

P/N: 0161750 | BTH 60-60

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Payload:	120 kg
Capacity:	2000 W
Nominal current:	8,6 A
Protection class:	Class I
Frequency:	50 Hz
Weight:	34 kg
Width:	795 mm
Depth:	747 mm
Height:	730 mm

Mobile cutlery soak sink for pre-soaking dirty cutlery items.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Closed design with seamless and jointless welded deep-drawn and fully isolated well with drain valve operated from outside, threaded connection metal-to-metal sealing as per EN 10226. Residue-free emptying of well thanks to special inclination of base. Standard perforated plate protects well base from direct contact with insert baskets. Heating through stainless steel tubular heating element with infinitely variable thermostat control. Electrical connection via dimensionally stable spiral cable with angled two-pin earthed angle plug and dummy socket on operating side. Welded frame rack made of square tubes as trolley base. 4 swivelling polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Easy handling thanks to two ergonomically-shaped polypropylene push bars that serve as additional bumpers. Trolley runs on 4 swivel casters of which 2 with total locks, \varnothing 4.9" (125 mm), with pin fastening.

The Hupfer cutlery immersion trolley BTH 60-60 has an installation height that makes it outstandingly suited to pushing it under work tables and conveyor systems, in particular when cutlery lifting magnets are used.

Time and date of the request:
17.08.2025, 21:39:03

All information / dimensions are approximate, technical changes reserved. © Hupfer