

Mobile bain marie

P/N: 0164197 | SPA 2EB

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity:	2 × GN 1/1-200 or smaller
Payload:	110 kg
Capacity:	1400 W
Supply voltage:	AC 220-230 V
Nominal current:	6,0 A
Protection class:	Class I
Frequency:	50/60 Hz
Weight:	36 kg
Width:	677 mm
Depth:	900 mm
Height:	939 mm

Heated mobile bain-marie for transporting and dispensing prepared food in GN containers.

High-quality stainless steel trolley in stable, self-supporting and hygienic design. Enclosed design with seamlessly welded, fully insulated wells, can be heated wet or dry, with deep drawn level indicator for wet heating. Each well can hold a GN 1/1-200 or smaller container. The wells are specifically sloped at the bottom so that they can be completely drained via an externally adjustable 1/2" ball valve. Drain cock protected from accidental opening, each setting easily visible even at a distance. Heated by stainless steel tubular heating element, can be operated at the front via on/off switch with integrated indicator light and thermostatically controlled by variable, ergonomically designed temperature controller, also easily seen at a distance, with temperature limiter as per VDE. Power supplied by a sturdy retractable helix cable with angle plug and holder on the back. Firmly welded frame made of rectangular tube with welded-on shelf with all-round edged downfold, with board with circumferential profile edge all round the bottom of the trolley. Four solid polyethylene disc bumpers at the bottom and two polymer corner bumpers on the top of the body with integrated, ergonomically designed push handles, for all-round collision protection of the device and walls. Mobile trolley with 4 swivel castors, including 2 with total brakes, \varnothing 125 mm, with pin fixing.

The Hupfer mobile bain marie SPA EB-2 has two push handles installed on the corners of the unit to ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food

Time and date of the request: 08.04.2025, 22:21:01 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

Mobile bain marie

P/N: 0164197 | SPA 2EB

HUPFER
we make work flow

distribution.

Time and date of the request:
08.04.2025, 22:21:01

All information / dimensions are approximate, technical changes reserved. © Hupfer