

Mobile bain marie for mobile counters

P/N: 0164208 | SPA 3EB LS

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity:	3 × GN 1/1-200 or smaller
Payload:	165 kg
Capacity:	2100 W
Supply voltage:	AC 220-230 V
Nominal current:	9,0 A
Protection class:	Class I
Frequency:	50/60 Hz
Weight:	46 kg
Width:	677 mm
Depth:	1236 mm
Height:	900 mm

Heated mobile bain-marie for transporting and dispensing prepared food in GN containers, especially for mobile counters.

High-quality stainless steel trolley in stable, self-supporting and hygienic design. Enclosed design with seamlessly welded, fully insulated wells, can be heated wet or dry, with deep drawn level indicator for wet heating. Each well can hold a GN 1/1-200 or smaller container. The wells are specifically sloped at the bottom so that they can be completely drained via an externally adjustable 1/2" ball valve. Drain cock protected from accidental opening, each setting easily visible even at a distance. Heated by stainless steel tubular heating element, can be operated at the side via on/off switch with integrated indicator light and thermostatically controlled by variable, ergonomically designed temperature controller, also easily seen at a distance, with temperature limiter as per VDE. Power supplied by a sturdy retractable helix cable with angle plug and holder on the left narrow side. Firmly welded frame made of rectangular tube with welded-on shelf with all-round edged downfold, with board with circumferential profile edge all round the bottom of the trolley. Four solid polyethylene disc bumpers at the bottom for all-round protection of the device and walls from damage. There is an additional bumper with integrated finger grip above the controls. Trolley on 4 swivel castors, including 2 with total brakes, ø 125 mm, with pin fixing.

The Hupfer mobile bain marie SPA EB-3 LS is specially equipped with a recessed grip above the operating elements on the long side, and a power feed installed on the front side, for use at docking counters. The

Time and date of the request:
24.04.2025, 20:16:29

All information / dimensions are approximate, technical changes reserved. © Hupfer

Mobile bain marie for mobile counters

P/N: 0164208 | SPA 3EB LS

HUPFER
we make work flow

installation height of 900 mm is the standard working height in food distribution.

Time and date of the request:
24.04.2025, 20:16:29

All information / dimensions are approximate, technical changes reserved. © Hupfer