

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Capacity:	Porcelain standard 1/4 up to 416 bowls
Modular dimension:	75 mm
Insertion type:	Crosswise insertion
Temperature range:	digital controller, precise to the degree
Payload:	320 kg
Capacity:	600 W
Cooling capacity:	1039 Watt
Supply voltage:	AC 220-230 V
Nominal current:	16.00 A
Frequency:	50-60 Hz
Width:	1114 mm
Depth:	798 mm
Height:	1973 mm

Two refrigerated compartments with rail pairs for keeping food cool according to HACCP specifications. Powerful air curtain refrigeration for cooling even when the front shutters are open for portioning food. Fan-assisted cooling for even and constant temperature distribution on all levels of the interior. On the front of each compartment an aluminium shutter with handle for one-handed use. Shutters can be opened separately on each compartment. Polymer rails ensure that shutters do no jam. Self-supporting torsionally rigid structure made of high quality stainless steel. Double-walled housing isolated on all sides with CFC-free, fire-retardant material. Housing with smooth stainless steel surfaces. On each corner a vertical ergonomic handle made of round stainless steel tube. Simple and ergonomic manoeuvring of the cart with two hands at any handle height. Housing protected from damage by polymer bumper strips round the entire chassis and top. Protruding edges and attachments on the housing also inside the area protected by the bumper strips. Additional bumper on the rear at 150 mm level with common kitchen appliances. Front with built-in operating and control unit with digital temperature display, on/off switch and buttons for setting the temperature. Hygienic interior with smooth stainless steel surfaces. Air baffles in the rear and on the base can be removed for cleaning the interior. Heat exchanger for refrigeration installed behind removable rear panel. Each compartment has two removable stainless steel uprights with welded brackets for inserting trays, grilles or containers. Interior can be completely emptied and can be cleaned very easily and hygienically. Optionally two LED light strips for lighting the interior.

Time and date of the request:
04.05.2024, 11:30:51

All information / dimensions are approximate, technical changes reserved. © Hupfer

CoolMultiMobil

P/N: 0164476-VK | CMM UK

HUPFER
we make work flow

without glare. Power club with sturdy cable screw connection and strain relief. Smooth power cable, approx. 1500 mm long. Stainless steel universal holder on the connection side for safely hanging the plug during transport. Technical compartment for refrigeration system below the cooling compartment. Inspection opening with triangular latch on the front for easy access to the refrigeration system.

Time and date of the request:
04.05.2024, 11:30:51

All information / dimensions are approximate, technical changes reserved. © Hupfer