## Swivel castor with lock Ø 125 mm

P/N: 0191445150 | LR Poly/St RI1/125 mF





## Technical data

Payload:

100 kg

Weight:

0.5 kg

Width:

130 mm

Depth:

59 mm

Height:

161 mm

Similar to illustration, technical modifications reserved. Without decoration.

The swivel castor with a brake is designed for attachment to mobile devices. The swivel castor with a brake enables the mobility, steerability, and controllability of the devices.

The easy-running swivel castor with brake made of high-quality plastic and metal parts from galvanised steel is corrosion-protected and is designed for attachment to movable equipment. The Hupfer swivel castor ensures the mobility of movable devices. The effortless turning, steering, and positioning of the devices using the swivel castors increase the efficiency and safety of performing tasks in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for effortless handling of the equipment, even with heavy loads. The sliding bearing enables almost silent and smooth mobility. The brakes ensure the securing and stabilisation of the device's position. The swivel castor is securely mounted to the device via a rear hole, providing stability.

- Durable plastic housing ensures longevity
- Swivel bearings with double ball race allow effortless movement and precise control
- Plain bearings provide near-silent and smooth operation
- Locking mechanisms guarantee the securing and stabilisation of the device's position

Time and date of the request: 10.04.2025, 09:33:25

All information / dimensions are approximate, technical changes reserved. © Hupfer