

Swivel castor with lock Ø 125 mm

P/N: 0191445155 | LR Poly/St Rz1/125 mF

HUPFER
we make work flow



Technical data

Payload:	100 kg
Weight:	0.6 kg
Width:	130 mm
Depth:	59 mm
Height:	222 mm

Similar to illustration, technical modifications reserved. Without decoration.

The swivel castor with a brake is used for attachment to movable equipment. The swivel castor with a brake allows for the mobility, steerability, and controllability of the equipment.

The easy-running swivel castor made of high-quality plastic with galvanized steel metal parts is rust-free and is designed for attachment to mobile devices. The Hupfer swivel castor ensures the mobility of mobile devices. The effortless turning, steering, and positioning of the devices using the swivel castors increase the efficiency and safety of performing tasks in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for effortless handling of the devices, even with heavy loads. The plain bearing enables almost silent and smooth mobility. The swivel castor is securely mounted to the device using a round pin, ensuring stability.

- The impact-resistant plastic housing ensures rust resistance and durability. - Swivel bearings with double ball rings enable effortless movement and precise control. - Sliding bearings and thread protection provide near-silent and smooth operation. - Locking devices guarantee the securing and stabilisation of the device's position.

Time and date of the request:
04.04.2025, 09:46:47

All information / dimensions are approximate, technical changes reserved. © Hupfer