

ISOBOX food transport trolley

P/N: 0223050 | Isobox Basic 30xGN-1/1

HUPFER
we make work flow



Technical data

Width: 550 mm

Depth: 730 mm

Height: 1640 mm

Similar to illustration, technical modifications reserved. Without decoration.

ISOBOX® Mobil Basic for transporting and dispensing meal components in GN containers or on GN 1/1 trays

Fully enclosed transport trolley in light and robust sandwich design made of aluminium sections with two compartments one above the other. Double-walled hinged doors open to 270°, held open by magnets. Doors as well as closed rear and side walls in a choice of RAL colours. Interior with two compartments one above the other for GN 1/1 containers or trays inserted lengthwise. Beaded side walls and a vertical profile as a tray stop on the rear of the interior made of completely pigmented polystyrene, suitable for all foodstuffs, can be used at any temperature from -10° to +70°C. Eight solid, round polypropylene bumpers at the lower and upper corners of the body very effectively protect both the trolley and the walls of the building from damage. Vertical handrails on the corners for easy manoeuvrability. Trolley moves on 2 swivel castors with total brakes, 2 fixed castors, with bolt hole attachment, 125 mm diameter.

The HUPFER® - ISOBOX® Mobil Basic/V 2/30 37.5 is highly flexible for the neutral transport of hot and passively cooled food. The four handrails on the corners of the trolley ensure optimal handling.

Time and date of the request:
20.11.2024, 05:19:31

All information / dimensions are approximate, technical changes reserved. © Hupfer