Fully-welded sterile goods transport cart

P/N: 7504646 | STW/VV 9StE 1249/754/1464





Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Cleaning classification: Suitable for washing devices

Capacity: 9 × StU

Payload: 200 kg

Weight: 119.087 kg

Width: 1249 mm

Depth: 1464 mm

Height: 790 mm

Transport trolley for transport and storage of sterile supplies in containers or baskets. 160 mm stainless steel castors as standard. With sign holder.

Trolley made entirely of high-quality stainless steel, robust, self-supporting and hygienic design. Single-walled trolley structure closed on all sides in fully welded design, suitable for washing devices. Double-walled double-wing doors with continuous seals, can be opened by 270°, automatic closing mechanism, operation with one hand. Door lock through integrated 2-point locking. Interior with removable solid shelves that are height-adjustable within the entire interior height. Four continuous vertical push bars (2 per side) for manoeuvring even with the doors open. Bumper protective feature provided by robust, continuous bumper strip that is effective also with the doors open, with frontal recesses for connecting a towing device to the chassis. Trolley runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and several screws.

Time and date of the request: 29.04.2024, 19:07:36

All information / dimensions are approximate, technical changes reserved. © Hupfer