

Hot-Cold-Plate GN-1/1 with glass surface for central refrigeration for installation, without install

HUPFER
we make work flow

P/N: 8900214 | KWP 1/1 GLA ZK/R513a EW1

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Payload:	9 kg
Capacity:	1840 W
Supply voltage:	AC 220-230 V
Nominal current:	8.00 A
Protection class:	Klasse 1
Frequency:	50-60 Hz
Weight:	12.989 kg
Width:	343 mm
Depth:	543 mm
Height:	201 mm

Hot and cold plate for the presentation and serving of hot and cold food. Device for installation in a counter or mobile bain marie.

High-quality stainless steel unit in stable, self-supporting and hygienic design. A hot and cold plate with a cover plate that ensures optimum temperature distribution due to its excellent temperature distribution is integrated in the cover. The use of a control system with digitally programmable temperatures and cooling pipes for connection to the on-site central cooling system. Self-regulating PTC heating elements with a short heat-up phase and a constant linear temperature curve on the other hand additionally enables a fast change between cold and hot operation in the range from -5°C to +140° C.

Time and date of the request:
20.11.2024, 01:40:02

All information / dimensions are approximate, technical changes reserved. © Hupfer