Hot-Cold-Plate GN-3/1 sintered ceramic top for central refrigeration for installation, without frame



P/N: 8900241-01 | KWP CER ZK GN 3/1



Technical data

Pavload.

Payloau.	27 Kg
Capacity:	2070 W
Supply voltage:	AC 220-230 V
Nominal current:	9,0 A
Protection class:	Class I
Frequency:	50/60 Hz
Weight:	26.205 kg
Width:	990 mm
Depth:	543 mm
Height:	201 mm

27 kg

Similar to illustration, technical modifications reserved. Without decoration.

Hot and cold plate for the presentation and serving of hot and cold food. Device for installation in a counter or mobile bain marie.

High-quality stainless steel unit in stable, self-supporting and hygienic design. A hot and cold plate with a cover plate that ensures optimum temperature distribution due to its excellent temperature distribution is integrated in the cover. The use of a control system with digitally programmable temperatures and cooling pipes for connection to the on-site central cooling system. Self-regulating PTC heating elements with a short heat-up phase and a constant linear temperature curve on the other hand additionally enables a fast change between cold and hot operation in the range from -5°C to +140° C.

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer06.04.2025, 19:59:59

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.com